# Carrier Inverter Hi Wall Air Conditioner



# Why Choose Carrier **Air Conditioners?**

#### **History and Reputation**

On July 17, 1902, Willis Carrier designed the first modern air conditioning system to address a challenge at the Sackett & Wilhelms printing plant in Brooklyn, New York City. This groundbreaking invention marked the beginning of a transformative era, fundamentally improving the way we live, work, and play.

With over a century of experience, Carrier has earned a reputation for being a pioneer in Heating Ventilation and Air Conditioning (HVAC) technology. Consumers can trust the reliability and durability associated with a brand that has consistently set industry standards for quality.





### **Energy Efficiency**

Carrier's focus on energy efficiency is evident through the integration of innovative technologies, design elements, and smart features in its air conditioning systems along with Featuring remarkable Govt. Zoned Energy Star Ratings (ZERL). As environmental concerns and energy conservation become increasingly significant, Carrier remains dedicated to delivering solutions that prioritize efficiency, sustainability, and overall performance.

\*Carrier QAG026N8 Cooling

## **Superior After Sales Service**

At Carrier, we are committed to delivering exceptional after-sales service through our responsive customer support team, providing efficient technical assistance for installations and troubleshooting. We ensure the customer support team is knowledgeable and welltrained, addressing inquiries promptly and effectively.







# Features Checklist -**Carrier Indigo**

Comfort Feature	s							
Turbo	✓							
Silence Mode	✓							
Follow Me	<b>√</b>							
Auto Restart	<b>√</b>							
Fast Cooling & Heating	<b>√</b>							
Anti-Cold Air Function	✓							
Wind Avoid Me	✓							
Energy Saving Feat	ures							
GA Compressor Frequency Control	<b>√</b>							
Gear operation	✓							
1%~100% Grades indoor Fan Speed	/							
9 Grades Outdoor Fan Speed	/							
X-Eco Mode	✓							
8° Heating	✓							
Sleep Mode	✓							
Convenience Featu	ires							
Multi Controllers	✓							
2-way Draining	✓							
Louver Position Memory	✓							
Manual On & Off Button	✓							
Open Terminal Block	/							
Reliability Featur	es							
Refrigerant Leakage Detection	<b>✓</b>							
Fire Proofing E Box	/							
Low Ambient Cooling & Heating	/							
Auto Defrosting	/							
Intelligent Dusting Switch	/							
Health Features								
HD Dust Filter	/							
Fresh Filter	0							
Active Clean	/							
Ionizer	0							
UV-Lamp	✓							

O - Optional

#### **Features**



#### **Efficiency Meets Luxury**

Featuring remarkable Zoned Energy Star Ratings (ZERL), the latest Inverter Hi Wall series, Indigo, offers exceptional performance dynamics. Equipped with Wi-Fi ready technology for optimal control flexibility, Active Energy Control, and a self-cleaning feature in the outdoor unit, the Carrier Indigo ensures a premium experience within your living spaces and beyond.

#### **High Achiever**

Whether in the bedroom, home office, study, kids room, or guest room, the Indigo series 2.6kW model boasts an impressive 6.5 ZERL star rating for cooling. This ensures excellent air conditioning, enabling your family to unwind, stay comfortably cool, and embrace energy efficiency - a true win-win!

#### **Carrier Comfort Connect**

Manage your climate effortlessly from anywhere using the Wi-Fi Ready APP on your smartphone. Easily schedule weekly timers through the smartphone APP. With a simple swipe, you can power the air conditioner on/off, choose the desired mode and temperature even before you get home.

### **Intelligent Dusting Switch**

Apart from the innovative bionic fan blades, the DC motor is designed to rotate continuously in reverse, effectively eliminating sand and dust, thereby ensuring a clean compressor and facilitating smooth operation.

# **Active Clean**

The Active Clean Technology effectively eliminates dust, mold, and grease that often accumulate on the indoor unit heat exchanger. This process involves automatically generating additional condensate water, freezing it, and subsequently thawing and airing it dry. This robust cleaning cycle takes 20-45 minutes - now that's clean!





\*6.5 stars rating on 2.6kW system Cooling







## **Features**

#### **Breeze Away**

Take control of your comfort and avoid direct breeze exposure by effortlessly adjusting the breeze direction with the remote.



#### Follow Me

When this function is turned on, the room temperature sensor within the remote controller takes over from the indoor unit's sensor. It adapts the room temperature, following your lead with the remote controller, whether you're taking it easy on the couch or cooking up a treat in the kitchen.



#### **Sleep Mode**

During cooling mode, the set temperature increases by 1°C every hour (up to a maximum of 30°C). After 2 hours, the temperature adjustment stops, and the indoor fan remains fixed at low speed.

In heating mode, the set temperature decreases by 1°C every hour (no less than 17°C). After 2 hours, the temperature adjustment stops, and the indoor fan remains fixed at low speed, with an available anti-cold-air function.



### **Low Ambient Heating & Cooling**

Wide range of ambient operation for Heating & Cooling. The system will continue to provide cooling even at temperatures of up to 50°C and will continue heating even at temperatures as low as -15°C.



## **UV Lamp**

The UV lamp helps keep your system clean by eradicating bacteria, mold, and mildew so they do not become ariborne and circulate throughout your home.



# Specifications Indigo





	M	Indoor	42QAG020N8	42QAG026N8	42QAG035N8	42QAG050N8	42QAG060N8	42QAG070N8	42QAG080N8	
	Model Number	Outdoor	38QAG020N8	38QAG026N8	38QAG035N8	38QAG050N8	38QAG060N8	38QAG070N8	38QAG080N8	
	Refrigerant Type					R32				
	Refrigerant amout	gm	620	90	00	12	60	14	.00	
	Power Supply	Volts- Phase- Hz			22	20-240 <b>V</b> , 1Ph,50H	łz			
	Capacity - Rated	kW	2.00	2.65	3.50	5.00	6.00	7.00	8.00	
	Capacity - Range (Min / Max)	kW	0.74/3.43	0.98/3.90	1.00/3.79	2.35/5.83	2.76/6.00	3.20/8.00	3.20/8.00	
ö	Power Input - Rated	kW	0.45	0.53	0.79	1.36	1.77	2.00	2.35	
COOLING	Power Input - Range	kW	0.16/1.06	0.18/1.05	0.18/1.03	0.48/1.88	0.58/1.88	0.67/2.65	0.67/2.65	
ດ	Seasonal Efficiency (Hot / Average / Cold)	Star Rating	5.5 / 5 / 5	6.5 / 6 / 6.5	5/5/5	4/4/4	4/4/4	3.5 / 3.5 / 3.5	3.5 / 3.0 / 3.5	
	Operating Current	А	2.01	2.50	3.50	6.00	7.90	8.62	10.00	
	Capacity - Rated	kW	2.20	2.75	3.75	5.35	6.20	7.6	8.2	
	Capacity - Range (Min / Max)	kW	0.86/4.36	1.02/4.21	1.06/4.55	2.41/6.03	2.41/6.40	2.26/8.82	2.26/8.82	
EATIN	Powr Input - Rated	kW	0.46	0.53	0.83	1.46	1.82	2.07	2.30	
	Powr Input - Range	kW	0.16/1.29	0.16/1.49	0.17/1.45	0.46/2.00	0.46/2.00	0.47/2.91	0.47/2.91	
G	Seasonal Efficiency (Hot / Average / Cold)	Star Rating	3.5 / 3 / 2.5	4 / 3.5 / 3	4/3/2.5	3 / 2.5 / 2	3 / 2 / 1.5	3 / 2.5 / 2	3 / 2.5 / 2	
	Operating Current	А	2.12	2.30	3.68	6.52	8.20	9.04	9.98	
=	Dimension (W×D×H)	mm	729x200x292	802x20	00x295	971x228x321		1082x234x337		
ğ	Net Weight	kg	8.0	8.	5	11.2		13.5		
ŎR	Cooling Airflow (Hi/Mi/Lo)	l/s	128/94/75	139/100/83	147/106/86	222/16	67/139	335/235/186		
INDOOR UNIT	Moisture Removal	L/hr	0.48	0.50	0.87	1.73	2.47	2.24	2.92	
٦	Sound Pressure (Hi/Mi/Lo) - 1m	dB(A) (@spl)	38/31.5/30	37/31/29	39/32.5/30	44.5/3	8/34.5	50/42/26.5		
	Dimension (W×D×H)	mm	765x303x555	805x33	30x554		890x3	42x673		
	Net Weight	kg	26.5	32	2	37	.9	42.4		
FID	Inverter Compressor	Rotary				SINGLE				
DO	Fan Motor Output	W		34			8	30		
유	Cooling (Sound Pressure) (H) at 1m distance	dB(A) (@spl)	55.5	54	55.5	59	.5	60	).5	
Z Z	Cooling Sound Power (H)	dB(A)	54	58	59	66	65	65	67	
15	Cooling Usable Temperature Range	Celsius				0~50				
	Heating Usable Temperature Range	Celsius				-15~24				
	Liquid Line Ø/Gas Line Ø	mm		6.35 / 9.52		6.35 /	12.7	6.35	/ 15.9	
7	Coupler Style					Flare Joint				
PIPE SIZE	Minimum Length	m				3				
SIZ	Maximum Length	m		25		3	0	5	0	
H	Pre-Charge Length	m				5				
	Maximum Height Difference (Above/Below)	m		10		2	0	2	5	



Demand Response Enabled



Golden Fin Protective Coating



Compound Filter



Filter Cleaning Reminder



Sleep Mode Do Not Disturb



2-way Draining



Silent



Auto Restart Function



Louver Position Memory



Timer





# **Capacity Guide & Star Rating**



#### Great for the Study or Home Office | 2.0 kW

Indoor Model	Outdoor Model	Zone	Sizing	Cooling Stars	Heating Stars
42QAG020N8	38QAG020N8	НОТ	9-12m <sup>2</sup>	5.5 <b>** ** *</b>	3.5
		AVG.	9-14m <sup>2</sup>	5.0 ★★★★	3.0 ★★★
		COLD	9-16m <sup>2</sup>	5.0 ★★★★	2.5

#### Kids or Guest Room | 2.6 kW

Indoor Model	Outdoor Model	Zone	Sizing	Cooling Stars	Heating Stars
42QAG026N8	38QAG026N8	НОТ	9-18m <sup>2</sup>	6.5 ★★★★★★	4.0 ★★★★
	<b>6</b>	AVG.	9-20m <sup>2</sup>	6.0 ★★★★★	3.5
		COLD	9-23m <sup>2</sup>	6.5 ★★★★★★	3.0

#### Master Suite | 3.5 kW

Indoor Model	Outdoor Model	Zone	Sizing	Cooling Stars	Heating Stars
42QAG035N8	38QAG035N8	НОТ	17-26m <sup>2</sup>	5.0 ★★★★★	4.0 ★★★★
		AVG.	17-28m <sup>2</sup>	5.0 ★★★★★	3.0 ★★★
		COLD	17-31m <sup>2</sup>	5.0 ★★★★★	2.5

#### Ideal for Sitting Room or Home Theatre | 5.0 kW

Indoor Model	Outdoor Model	Zone	Sizing	Cooling Stars	Heating Stars
42QAG050N8	38QAG050N8	НОТ	25-36m <sup>2</sup>	4.0 ★★★★	3.0 ★★★
	<b>6</b>	AVG.	25-40m <sup>2</sup>	4.0 ★★★★	2.5
		COLD	25-45m <sup>2</sup>	4.0 ★★★★	2.0 ★ 🗙

#### Family Rumpus Room | 6.0 kW

Indoor Model	Outdoor Model	Zone	Sizing	Cooling Stars	Heating Stars
42QAG060N8	38QAG060N8	НОТ	35-43m <sup>2</sup>	4.0 ★★★★	3.0 ★★★
		AVG.	35-48m <sup>2</sup>	4.0 ★★★★	2.0
		COLD	35-54m <sup>2</sup>	4.0 ★★★★	1.5

#### **Dinning or Entertainment Room | 7.0 kW**

Indoor Model	Outdoor Model	Zone	Sizing	Cooling Stars	Heating Stars
42QAG070N8	38QAG070N8	НОТ	38-49m <sup>2</sup>	3.5 ★ 🛧 🛨	3.0 ★★★
	<b>6</b>	AVG.	38-54m <sup>2</sup>	3.5	2.5
		COLD	38-62m <sup>2</sup>	3.5	2.0

#### Multi Purpose Space | 8.0 kW

mater alposo opaso polo kit								
Indoor Model	Outdoor Model	Zone	Sizing	Cooling Stars	Heating Stars			
42QAG080N8	38QAG080N8	НОТ	45-61m <sup>2</sup>	3.5	3.0 ★★★			
		AVG.	45-67m <sup>2</sup>	3.0 ★★★	2.5			
		COLD	45-71m <sup>2</sup>	3.5	2.0 ★ 🛨			

# Carrier Inverter Hi Wall Air Conditioners

AHIC is committed to continuously improving its product to ensure the highest quality and reliability standards, and to meet local regulations and market requirements.

Product specifications in this brochure are only indicative and are subject to change. These are not intended to be used in place of the engineering or installation book.

All features and specifications are subject to change without prior notice.

All images provided in this catalogue are used for illustration purposes only.

Cooling and heating capacities mentioned for the products are nominal capacities at standard operation conditions.

Equipment rates in accordance with MEPS 3823.2-2011 E&OE Date: January 2024





SALES AND SERVICE: **13 COOL (13 2665)**AHIC (Australia) Pty Ltd- Level 1, 152 Wellington Road, Clayton, VIC 3168
ABN 37 606 792 456 AU 22499

carrierair.com.au

